### **MANOMAY**









#### 3MP Resolution

For better clarity and detailed surveillance



#### Two Way Audio Intercom

Built-in Speaker and Microphone with echo cancellation








IR Mode / Full Colour / Smart Mode



### Alexa Support

Watch Camera Footage on your Alexa show Device







## **Customized Audio Alarm**

Human detection based recording and push notifications



# Human & Motion Tracking

Al Based Humanoid Detection with Motion Tracking







## 6 Preset Location Points

Preset locations for easy and effective surveillance



#### Smart Notification on Mobile App

Push notifications on mobile app with snapshots







## H.265 Video Compression

High quality video compression for optimum utilization of storage space



#### Manomay App

30 Days Cloud Recording

**FREE** 

•REC

### Configure your Camera in just 3 Quick Steps



**Download**Manomay App from
App Store or Play Store

Scan QR Code

In app, **Tap "+"** sign & Scan QR Code from back of the camera



instructions and your camera is ready to use

#### 3MP 4G Protect Pro Mini Pan-Tilt Camera



Mirror/Flip

Al Features

Monitoring

Protocol

Electronic Shutter

On Screen Display (OSD)

#### **Features**

- 3MP (2304 x 1296) Resolution
- All Time Colour Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Horizontal Rotation : 270°, Vertical Rotation : 90°
- Support 10x Digital Zoom
- 6 Preset Points for favorite location
- Smart Human Detection, Motion Detection, Motion Tracking
- Mobile Notification on Human & Motion Detection
- Customized Pre-Recorded Voice Alarm
- Support Micro SD Card up-to 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring : Mobile / PC Software (Manomay)
- IP66 Waterproof Rating, 4000 Lightening Protection.
- Alexa Support



Technical Specification         M1005-A           I mage Sensor         1/2.9" CMOS Sensor           Resolutions         3MP (2304 x 1296)           Lens         4mm           IR LED         12 Array           IR Distance         30 Meters           White LED         12 White Array           White LED Distance         20 Meters           Viewing Angle         Horizontal: 68", Vertical: 53", Diagonal: 81"           Video Streaming         Main Stream: 2304 x 1296 / 15 fps           Audio Input/Output         Two way audio, Built in microphone and speakers           Audio Compression Standard         AAC / G711A           Pan-Tilt Angle         Pan: 0" - 270", Tilt: 0" - 90" Horizontal speed 20%S, Vertical Speed 10%S           Zoom         10x Digital           Light Mode         Full Cotour / Infrared / Intelligent           DNR         3D Digital Noise Reduction           Day & Night         IR-cut Auto ICR           Min Illumination         Colour: 0.01 Lux, Black & White: 0.001 Lux           WDR         D-WDR		
Image Sensor Resolutions  I/2.9" CMOS Sensor Resolutions  3MP (2304 x 1296)  Lens  4mm  IR LED 12 Array  IR Distance 30 Meters  White LED 12 White Array  White LED Distance 20 Meters  Viewing Angle Horizontal: 68°, Vertical: 53°, Diagonal: 81°  Video Streaming Main Stream: 2304 x 1296 / 15 fps  Sub Stream: 640 x 360 / 15 fps  Audio Input/Output Two way audio, Built in microphone and speakers  Audio Compression Standard AAC / G711A  Pan-Tit Angle Pan-Tit Angle Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom 10x Digital  Light Mode Full Colour / Infrared / Intelligent  DNR 3D Digital Noise Reduction  Day & Night Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance	Technical Specification	
Resolutions Lens 4mm  IR LED 12 Array  IR Distance 30 Meters White LED 12 White Array White LED 12 White Array  White LED 12 White Array  White LED Distance 20 Meters Viewing Angle Video Streaming Main Stream: 2304 x 1296 / 15 fps Sub Stream: 640 x 360 / 15 fps  Audio Input/Output Audio Compression Standard AAC / G711A Pan-Titt Angle Pan-Titt Angle Pan: 0° - 270°, Titt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom 10 x Digital Light Mode DNR 3D Digital Noise Reduction Day & Night IR-cut Auto ICR Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux White Balance	Product Code	M1005-A
Lens  Lens  HR LED  12 Array  IR Distance  White LED  12 White Array  White LED Distance  Viewing Angle  Video Streaming  Main Stream: 2304 x 1296/15 fps Sub Stream: 640 x 360/15 fps  Audio Input/Output  Two way audio, Built in microphone and speakers  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle  Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom  10x Digital  Light Mode  DNR  3D Digital Noise Reduction  Day & Night  Min Illumination  Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance	Image Sensor	1/2.9" CMOS Sensor
IR LED  IR Distance  White LED  12 White Array  White LED Distance  Viewing Angle  Video Streaming  Main Stream: 2304 x 1296 / 15 fps  Sub Stream: 640 x 360 / 15 fps  Audio Input/Output  Two way audio, Built in microphone and speakers  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle  Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20%S, Vertical Speed 10%S  Zoom  10x Digital  Light Mode  DNR  Day & Night  Min Illumination  Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance  Auto	Resolutions	3MP (2304 x 1296)
IR Distance White LED White LED 12 White Array White LED Distance 20 Meters Viewing Angle Horizontal: 68°, Vertical: 53°, Diagonal: 81° Video Streaming Main Stream: 2304 x 1296 / 15 fps Sub Stream: 640 x 360 / 15 fps Sub Stream: 640 x 360 / 15 fps Audio Input/Output Two way audio, Built in microphone and speakers Audio Compression Standard AAC / G711A Pan-Tilt Angle Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S Zoom 10x Digital Light Mode Full Colour / Infrared / Intelligent DNR 3D Digital Noise Reduction Day & Night IR-cut Auto ICR Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux White Balance Auto	Lens	4mm
White LED  White LED Distance  Viewing Angle  Video Streaming  Main Stream: 2304 x 1296 / 15 fps  Sub Stream: 640 x 360 / 15 fps  Audio Input/Output  Two way audio, Built in microphone and speakers  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle  Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20%S, Vertical Speed 10%S  Zoom  10x Digital  Light Mode  DNR  3D Digital Noise Reduction  Day & Night  Min Illumination  Colour: 0.01 Lux, Black & White: 0.001 Lux  Muto	IR LED	12 Array
White LED Distance  Viewing Angle  Video Streaming  Main Stream: 2304 x 1296 / 15 fps  Sub Stream: 640 x 360 / 15 fps  Audio Input/Output  Two way audio, Built in microphone and speakers  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle  Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom  10x Digital  Light Mode  DNR  3D Digital Noise Reduction  Day & Night  Min Illumination  Colour: 0.01 Lux, Black & White: 0.001 Lux  Muto	IR Distance	30 Meters
Viewing Angle  Video Streaming  Main Stream: 2304 x 1296 / 15 fps  Sub Stream: 640 x 360 / 15 fps  Audio Input/Output  Two way audio, Built in microphone and speakers  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle  Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom  10x Digital  Light Mode  Full Colour / Infrared / Intelligent  DNR  3D Digital Noise Reduction  Day & Night  IR-cut Auto ICR  Min Illumination  Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance  Auto	White LED	12 White Array
Video StreamingMain Stream: 2304 x 1296 / 15 fpsSub Stream: 640 x 360 / 15 fpsAudio Input/OutputTwo way audio, Built in microphone and speakersAudio Compression StandardAAC / G711APan-Tilt AnglePan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20%S, Vertical Speed 10%SZoom10x DigitalLight ModeFull Colour / Infrared / IntelligentDNR3D Digital Noise ReductionDay & NightIR-cut Auto ICRMin IlluminationColour: 0.01 Lux, Black & White: 0.001 LuxWhite BalanceAuto	White LED Distance	20 Meters
Sub Stream: 640 x 360 /15 fps  Audio Input/Output Two way audio, Built in microphone and speakers  Audio Compression Standard AAC / G711A  Pan-Tilt Angle Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20%S, Vertical Speed 10%S  Zoom 10x Digital Light Mode Full Colour / Infrared / Intelligent  DNR 3D Digital Noise Reduction  Day & Night IR-cut Auto ICR  Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto	Viewing Angle	Horizontal: 68°, Vertical: 53°, Diagonal: 81°
Audio Input/Output  Audio Compression Standard  AAC / G711A  Pan-Tilt Angle Pan-Tilt Angle Pan-O° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S  Zoom 10x Digital  Light Mode Full Colour / Infrared / Intelligent  DNR 3D Digital Noise Reduction  Day & Night IR-cut Auto ICR  Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto	Video Streaming	Main Stream : 2304 x 1296 / 15 fps
Audio Compression Standard  Pan-Tilt Angle Pan-Tilt Angle Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20%S, Vertical Speed 10%S  Zoom 10x Digital  Light Mode Full Colour / Infrared / Intelligent  DNR 3D Digital Noise Reduction  Day & Night IR-cut Auto ICR Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto		Sub Stream : 640 x 360 /15 fps
Pan-Tilt AnglePan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/SZoom10x DigitalLight ModeFull Colour / Infrared / IntelligentDNR3D Digital Noise ReductionDay & NightIR-cut Auto ICRMin IlluminationColour: 0.01 Lux, Black & White: 0.001 LuxWhite BalanceAuto	Audio Input/Output	Two way audio, Built in microphone and speakers
Zoom10x DigitalLight ModeFull Colour / Infrared / IntelligentDNR3D Digital Noise ReductionDay & NightIR-cut Auto ICRMin IlluminationColour: 0.01 Lux, Black & White: 0.001 LuxWhite BalanceAuto	Audio Compression Standard	AAC/G711A
Light Mode Full Colour / Infrared / Intelligent  DNR 3D Digital Noise Reduction  Day & Night IR-cut Auto ICR  Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto	Pan-Tilt Angle	Pan: $0^{\circ}$ - $270^{\circ}$ , Tilt: $0^{\circ}$ - $90^{\circ}$ Horizontal speed $20^{\circ}$ S, Vertical Speed $10^{\circ}$ S
DNR 3D Digital Noise Reduction  Day & Night IR-cut Auto ICR  Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto	Zoom	10x Digital
Day & Night IR-cut Auto ICR  Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux  White Balance Auto	Light Mode	Full Colour / Infrared / Intelligent
Min Illumination Colour: 0.01 Lux, Black & White: 0.001 Lux White Balance Auto	DNR	3D Digital Noise Reduction
White Balance Auto	Day & Night	IR-cut Auto ICR
	Min Illumination	Colour: 0.01 Lux, Black & White: 0.001 Lux
WDR D-WDR	White Balance	Auto
	WDR	D-WDR

On / Off

N1/ONVIF

Date, Time, & Title

Android, iOS, Windows (Manomay)

Motion Detection, Human Detection, Motion Tracking.

Auto

Slots		4G SIM Card / Micro SD Card
Storage		Support Micro SD Card up-to 256GB & Cloud Storage(Optional)
Connectors		RJ45 Port, Reset Button & DC Power Input
Connection	Mode	4G SIM & LAN Network
4G Frequer	ncy Band	FDD - LTE: B1/B3/B5/B8; TDD - LTE: B34/B38/B39/B40/B41
Light Mode	Indication	LED Blink : Not connected to Network, LED Continuous ON : Connected to Network
Power Inpu	t	DC: 12V/1A (DC 2.1mm Connector)
Power Con	sumption	≤5W
Working Te	emperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Te	mperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing M	aterial	Plastic (IP66)
Dimension		310mm x 112mm x 170(H x W x L)
Net Weigh	t .	0.474kg
Gross Weig	ght	0.680Kg

<sup>\*</sup>Note: Product Specifications are subject to change without prior notice.

### **Applications**



REMOTE LOCATIONS



REMOTE LOCATIONS



HOMES



CONSTRUCTION LOCATIONS



SHOPS



FARMS