MANOMAY

E SERIES Digital Signage

Manomay E Series 43 inch A Type DSS A9 2GB 16GB Non Touch

T260549-A

FEATURES

- Information can be broadcast, news released, products advertised, etc., digital signage, which is widely used in the fields of entertainment, finance, and traffic.
- Mobile application based contain push over the local wi-fi network
- cloud-based software solution that brings together content management and remote device management capabilities, allowing users to remotely manage hardware settings and troubleshoot issues while effortlessly creating and deploying content with no previous training needed.
- Metallic Body Appearance
 Light weight body with integrative design.



Cloud Based Content Management Software

Variable Materials

Static and dynamic materials, including pictures, Audio, Video, Scrolling Subtitle, PDF, Web page, Live Video, pop-up pictures, etc.

• Flexible Program Schedule

- > Free schedule and district display of multiple material.
- > Multiple play modes with customization support.

• Centralized Management


- > Remotely control and manage one or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview.
- > Remote program release and local (USB) program update.


Organization Permission

- > 5-level organization available for managing materials, programs, terminals, and users.
- > Create custom user with precise permission assignment. Multiple permission templates available.

• Multiple Security Safeguards

- > 3-level check of materials, programs, and schedules to prevent mistake release. Screen saver password to protect displaying.
- > Encryption of data storage and transmission to avoid data tampering.
- > With no default password, users can activate and set initial password to guarantee the password safety.
- > DSS Management Software to manage <2000pcs DSS Players





Technical Specification	
DISPLAY	
Diagonal Size Resolution	43 inch 1920 x 1080
Display Orientation Screen Type	Portrait TFT LCD (E-LED Backlight)
Aspect Ratio Display Area	16:9 940.89(V) × 529.25(H)
LCD Viewing Angle LCD Refresh Rate(Panel)	178° ≥8.5ms
LED Lifespan Working Hours	50,000hours, 7x16Hrs
Contrast Ratio Brightness	4000:1(Typ) ≥350cd/m²±10%
COMPUTING	
Android OS	9
RAM Internal Storage	2GB
Internal Storage CPU	16GB Hi352,Quad core, 32Bit, Cortex-A53 CPU,2.30GHz
GPU	ARM MaliTM-450
OSD Language	English, Arabic, Spanish, French, Italian, Japanese, Portuguese, Russian, etc
Video Format	Supports H.264/MVC/MPEG1/MPEG2/MPEG4/AVS+(AVS-P16)/VC-1/VP6/8 "1080P@60fps Video decoding; support, VP9 10bit, FHD@60fps Video decoding;Supports low latency video decoding
Audio Format	MPEG L1/L2;MP3;AAC_LC;HE_AACV2;LPCM;APE; FLAC; Ogg; AMR-NB/WB; G.711 Supports JPEG hardware decoding, with a maximum support of 64 million
Picture Format	pixels; Support "MJPEG Baseline decoding; Supported formats: 400/420/411/422/422T/444"
I/O PORT	
HDMI IN USB	1 2 (USB2.0)
AUDIO	
Dual Speakers	2 X 5W
NETWORK	
LAN in(RJ45)	10/100Mbps
Wake-on-LAN Wi-Fi	Yes IEEE802.11a/b/g, 2.4G
POWER	
Power Requirements	100V~240V AC, 50/60Hz
Power Consumption	75W
Power Consumption(Standby)	0.5W
Ultra-Quiet Fanless Design	Yes
ENVIROMENTAL	
Operating Temperature	0°C to 40°C(32°F to 104°F)
Storage Temperature	-15° to 55°C(-5°F to 131°F)
Operating Humidity	20% to 80% non-condensing humidity
Storage Humidity	20% to 90% non-condensing humidity
DIMENSION	(1) 2500 V (1) 500 1 v V (D) 75 mm
Product Dimension	(H) 1590 mm X (W) 599.1 mm X (D) 75 mm
PACKED CONTENTS	
Accessories	1 x Remote Controller, 2 x Key ,1 x Power Cable (Fixed With Device)

