

3MP 4G Protect Pro Mini Pan-Tilt Camera M1094S

FEATURES

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Horizontal Rotation:266°, Vertical Rotation: 90°
- Support 10x Digital Zoom
- 6 Preset Points for favorite location
- Smart Human Detection, Motion Detection, Smart Tracking
- Mobile Notification on Human & Motion Detection
- Support Micro Memory Card up to 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring : Mobile and Web CMS (Manomay Pro)
- IP66 Waterproof Rating, 4000 Lightening Protection.
- Alexa Support



4G SIM Support



3MP Resolution



256GB Memory Card



10X Digital Zoom



H.265 Compression



All Time Color



Smart Tracking



Cloud Recording



Location Presets

Technical Specification

| | |
|----------------------------|--|
| Product Code | M1094S |
| Image Sensor | 1/3" CMOS Sensor |
| Resolutions | 3MP (2304 x 1296) |
| Lens | M12 4MM Lens |
| IR LED | 6 Array |
| IR Distance | 30 Meters |
| White LED | 6 White Array |
| White LED Distance | 20 Meters |
| Video Streaming | H.264 / H.265 |
| Video Streaming | Main Stream : 2304 x 1296@15 fps Sub Stream : 800 x 448@15fps |
| Audio Input/Output | Two-way audio, Built-in microphone and speakers |
| Audio Compression Standard | AAC / G.711A |
| Zoom | 10x Digital |
| Light Mode | Full Color / Infrared / Intelligent |
| Day & Night | IR-cut Auto ICR |
| Min Illumination | Color : 0.01 Lux, Black & White : 0.001 Lux |
| DNR | 3D Digital Noise Reduction |
| White Balance | Auto |
| WDR | D-WDR |
| Mirror / Flip | On / Off |
| Electronic Shutter | Auto |
| On Screen Display (OSD) | Date, Time, & Title |

| | |
|--------------------------------|---|
| AI Features | Motion Detection, Human Detection, Smart Tracking. |
| Monitoring | Android, iOS, Web CMS (Manomay Pro) |
| Storage | Support Micro Memory Card up to 256GB & Cloud Storage (Optional) |
| Wired Network | RJ45 × 1 (10M / 100M Adaptive Ethernet Port) |
| 4G Frequency Band | FDD - LTE : B1 / B3 / B5 / B8; TDD - LTE : B34 / B38 / B39 / B40 / B41 |
| Protocol | ONVIF / RTSPS / RTSP / RTMPS / RTMP |
| Connectors | RJ45 LAN connector (100 Mbps) and DC Power Input |
| Slots | 4G SIM Card / Micro Memory Card |
| Button | Reset Button |
| Light Mode Indication | LED Blink : Not connected to Network, LED Continuous ON : Connected to Network |
| Power Input | DC : 12V/1A (DC 2.1mm Connector) |
| Power Consumption | ≤ 5W |
| Working Temperature / Humidity | 0-50° C RH Less than 95% (No Condensation) |
| Storage Temperature / Humidity | -20° C to 60° C / 20% to 90% RH |
| Housing Type | Plastic (IP65) |
| Dimension | 191mm X132mm X 170mm (H x W x L) |
| Net Weight | 550 Gms |
| Gross Weight | 800 Gms |

*** Note: Product specifications are subject to change without prior notice.**