

## 3MP Wi-Fi Protect Bot Pan-Tilt Camera M1078S

### FEATURES

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Horizontal Rotation : 352°, Vertical Rotation : 58°
- Support 10x Digital Zoom
- 6 Preset Points for favourite location
- Smart Human Detection, Motion Detection, Smart Tracking
- Mobile Notification on Human & Motion Detection
- Support Micro Memory Card up to 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring : Mobile and Web CMS (Manomay Pro)
- Alexa Support



3MP  
Resolution



Wi-Fi  
Connection



256GB  
SD Card



Smart  
Tracking



Two Way  
Audio Intercom



Works with  
Alexa



Cloud  
Recording



All Time  
Color

### Technical Specification

Product Code	M1078S
Image Sensor	1/3" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	M12 4MM Lens
IR LED	4 Array (Half LED)
IR Distance	20 Meters
White LED	4 White Array (Half LED)
White LED Distance	10 Meters
Video Compression Standard	H.264/H.265
Video Streaming	Main Stream : 2304 x 1296@15 fps Sub Stream : 800 x 448@15fps
Audio Input/Output	Two way audio, Built in microphone and speakers
Audio Compression Standard	AAC / G.711A
Zoom	10x Digital
Light Mode	Infrared / Full Color / Smart Night Vision
DNR	3D Digital Noise Reduction
Day & Night	IR-cut Auto ICR
Min Illumination	Color : 0.01 Lux, Black & White : 0.001 Lux
White Balance	Auto
WDR	D-WDR
Mirror/Flip	On / Off
Electronic Shutter	Auto

On Screen Display (OSD)	Date, Time, & Title
AI Features	Motion Detection, Human Detection, Smart Tracking.
Monitoring	Android, iOS, Web CMS (Manomay Pro)
Slots	Micro Memory Card
Connection Mode	Wi-Fi Network (IEEE802.11b / g / n)
Protocol	ONVIF / RTSPS / RTSP / RTMPS / RTMP
Storage	Support Micro Memory Card up to 256GB & Cloud Storage(Optional)
Button	Reset Button
Light Mode Indication	LED Blink : Not connected to Network, LED Continuous ON : Connected to Network
Power Input	DC : 5V/1A (Type-C)
Power Consumption	≤ 3W
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic
Dimension	123mm X 80mm X 80mm (H x W x L)
Net Weight	188 Gms
Gross Weight	345 Gms

**\* Note: Product specifications are subject to change without prior notice.**